

IL 17 (STA 22+50 TO STA 27+15)

\* VARIES SEE WIDENING PLAN

TYPICAL SECTION

	SUPERPAVE	SUPERPAVE	SUPERPAVE
	LEVELING	SURFACE	BASE
	BINDER		COURSE**
PG GRADE	PG 64-22	PG 64-22	PG 64-22
MAX % RAP			
ALLOWABLE*	15%	10%	25%
DESIGN AIR			
VOIDS	4.0% @ N70	4.0% @ N70	4.0% @ N50
MIXTURE		IL 12.5 OR	
COMPOSISION	IL 9.5	IL 9.5	IL 19.0
FRICTION		·	,
AGGREGATE		MIXTURE D	
PLANT LIMIT			:
CONTROLS	CLASS I	CLASS I	NON-CLASS I
DENSITY CONTROL	SATISFACTION OF	CORES/	SEE SPECIAL
METHOD	THE ENGINEER	NUCLEAR	PROVISIONS

\*IF RAP IS SELECTED, THE ASPHALT CEMENT GRADE MAY NEED TO BE ADJUSTED. THIS WILL BE DETERMINED BY THE ENGINEER.

\*\* TO BE USED FOR BITUMINOUS BASE COURSE 10" SUPERPAVE

REVISIONS
NAME DATE

TYPICAL SECTION

SCALE; VERT. DRAWN BY

JARY 13, 2006 32005/detalls.dgn